

FALCO 300 SPECIFICATIONS



The FALCO 300 electric catalytic oxidizer treats air streams contaminated with volatile organic compounds. Startup is fully automatic. Controllers accurately regulate input loading and temperatures. The controls adjust a FALCO Vapor Control Valve (VCV) to maintain safe maximum input concentrations. Automatic shutdown results if temperatures exceed limits.

The FALCO 300 has an efficient heat exchanger. A bypass valve adjusts heat recovery. Low heat recovery enables operation at high vapor concentration. High heat recovery minimizes energy use during operation at low input vapor concentration. At 600 ppmv (Gasoline) and 300 scfm, sufficient heat is recovered to preheat the inflow without supplementary electric energy.

The FALCO 300 has a massive catalyst volume for its rated capacity, providing longer life and poison resistance than monolith type catalysts. If necessary, the catalyst can be replaced on site in one hour. New catalyst is poured in after the old catalyst is removed with a shop vacuum.



- **CAPACITY** 100-350 CFM
- **MAXIMUM INPUT LOADING** 250 lb/day petroleum hydrocarbons @ 350 cfm
- **DESTRUCTION EFFICIENCY** Up to 99.5%
- **CATALYST TEMPERATURE RANGE** 330-620°C (626-1148°F)
- **CATALYST** Packed bed 2.5 cubic feet. Precious metal on 1/8" ceramic beads is standard. Optional catalyst for chlorinated solvents
- **HEAT EXCHANGER** Stainless steel spiral plate. 73% efficient at 300 scfm.
- **HEATER (Electric)** 56 amp @ 208 volts (20.3 kW) or, 64.6 amp @ 240 volts (27 kW) Solid State Control.
- **WEIGHT** 825 lb.
- **CONSTRUCTION** Stainless steel and aluminum
- **DIMENSIONS** 73" high (excluding 5' stack) X 70" long X 29" wide
Fits in the back of a pick-up truck
- **POWER REQUIREMENTS** 3 phase 208-240 Volt, optional 1 phase 240 Volt
- **APPROVALS** System is Factory Mutual approved for use in hazardous locations.
South Coast Air Quality Management District (SCAQMD) Certified Equipment Permit.