



PI = PRESSURE INDICATOR
 PSL = PRESSURE SWITCH, LOW (LOW INLET FLOW)
 TT = TEMPERATURE TRANSMITTER
 VFD = VARIABLE FREQUENCY DRIVE
 FA = FLAME ARRESTOR
 CATOX = CATALYTIC OXIDIZER
 HBV = HEAT EXCHANGER BYPASS VALVE
 FM = FLOW METER (PITOT TUBE)
 DPT = DIFFERENTIAL PRESSURE TRANSMITTER
 E-STOP = DILUTION BLOWER EMERGENCY STOP SWITCH

TT1 = CATALYST INLET TEMPERATURE
 TT2 = CATALYST EXIT TEMPERATURE
 TT3 = CATALYST INTERNAL TEMPERATURE

* OPTIONAL DEVICE, MAY NOT BE PRESENT
 ** CRITICAL SAFETY DEVICE

FALMOUTH PRODUCTS
 530 THOMAS LANDERS RD
 FALMOUTH, MA 02574
 PHONE: 508-548-6686
 FAX: 508-548-8144

FALMOUTH PRODUCTS

FALCO 600 – P&ID
 WITH VARIABLE
 FREQ. DRIVE

	NAME	DATE
DRAWN	MW	4/30/13
CHECKED		

SIZE	DWG. NO.	REV.
A	5091	C
SCALE: 1:1	WEIGHT:	SHEET 1 OF 1